


**BUILDING PLAN-PLUMBING**  
SCALE: 1/4"=1'-0"

**FLOOR PLAN NOTES**

- NEW ELECTRIC WATER HEATER ON WALL MOUNTED PLATFORM. ROUTE WASTE FROM T&P AND DRAIN VALVE TO MOP SINK OR FLOOR DRAIN AND INDIRECT WASTE.
- NEW RPZ BACKFLOW PREVENTER, WATTS 009 OR EQUAL. ROUTE WASTE FROM AIR-GAP FITTING OVER TO MOP SINK AND INDIRECT WASTE.
- 3/4" HOT AND COLD WATER DOWN AND IN WALL. CONNECT 1/2" HOT AND COLD WATER TO LAVATORY AND MOP SINK, AND 1/2" COLD WATER TO WATER CLOSET.
- PROVIDE SHUT-OFF VALVE AND DRAIN DOWN CONNECTION WITH 3/4" HOSE CONNECTION FOR WINTERIZATION. SLOPE ALL PIPING BACK TO DRAIN VALVE LOCATION.
- PROVIDE KEYED SHUT-OFF VALVES AND DRAIN DOWN CONNECTION IN VAULT BELOW FROST LINE FOR WINTERIZATION. PROVIDE BED OF CLEAN GRAVEL AND FILTER FABRIC AS REQUIRED. SLOPE PIPING BACK TO DRAIN VALVE LOCATION.
- COORDINATE WITH UNIVERSITY AND FACILITY MAINTENANCE FOR UTILITY ROUTING.



**WASTE/VENT RISER DIAGRAM**  
NO SCALE

**PLUMBING FIXTURE SCHEDULE**

MARK NO.	FIXTURE TYPE	MANUFACTURER	MODEL NO.	DESCRIPTION	MINIMUM CONNECTION SIZE			
					CW	HW	WASTE	VENT
WC-1	WATER CLOSET (ACCESSIBLE)	AMERICAN-STANDARD	215AA.004 "CADET PRO"	FLOOR MOUNTED FLUSH TANK, WHITE VITREOUS CHINA, HIGH EFFICIENCY (1.6 GPF), ELONGATED POWER WASH BOWL, FULLY GLAZED 2" TRAP W/ WAXY, CLOSE-COURED TANK, 16-1/2" RIM HEIGHT. ACCESSORIES: CHURCH 860SSCT WHITE OPEN FRONT SEA T LESS COVER WITH SELF SUSTAINING CHECK HINGES, BOLTS AND CAPS, LOOSE KEY ANGLE STOP AND CHROME-PLATED RISER. NOTE: HANDLE TO BE ON WIDE SIDE OF FIXTURE.	1/2"	-	4"	2"
L-1	LAVATORY (ACCESSIBLE)	AMERICAN-STANDARD	0355.012 "LUCERNE"	WALL HUNG, VITREOUS CHINA, 20" X 18", FRONT OVERFLOW, INTEGRAL BACK CHICAGO FAUCETS MODEL 802-KA/BOP FAUCET WITH CERAMIC OPERATING CARTRIDGE, 4" CENTERS, 4" INTEGRAL SPOUT, LEVER HANDLES. ACCESSORIES: PROVIDE LEONARD 170-LF LEAD FREE BRONZE THERMOSTATIC MIXING VALVE WITH 0.25 GPM MINIMUM FLOW RATE, INTEGRAL CHECK VALVES, DISCHARGE SET AT 105 F, MOUNTED DOWNSTREAM OF FIXTURE STOPS, WITH HOT AND COLD WATER PIPED TO VALVE, TEMPERED AND COLD WATER TO LAVATORY. CHICAGO FAUCETS MODEL 337-XOP OFFSET GRID DRAIN, 1-1/4" X 1-1/2" 17 GA. SEMI-CAST BRASS P-TRAP WITH CLEANOUT AND CHROME-PLATED RISERS WITH LOOSE KEY ANGLE STOPS. PROVIDE WITH FULLY MOLDED FLEXIBLE VINYL INSULATION KIT TO COVER TRAP, SUPPLIES AND STOPS, TRIBURO E-2 LAV GLAUD. NOTE: MOUNT FIXTURE RM 34" ABOVE FLOOR.	1/2"	1/2"	1-1/2"	1-1/2"
JS-1	JANITOR SINK	STERN-WILLIAMS	MTB-2424	SIZE 24" X 24" X 10", TERRAZZO SERVICE SINK WITH CAST BRASS DRAIN, STAINLESS STEEL STRAINER, 3" DRAIN CONNECTION. CHICAGO FAUCETS MODEL 897-CCP WITH QUARTZ OPERATING CARTRIDGE, VACUUM BREAKER SPOUT WITH PAIL HOOK AND WALL BRACE, 3/4" MALE HOSE THREAD OUTLET, 265 LEVER HANDLES, FLANGED ADJUSTABLE SUPPLY ARM AND INTEGRAL SUPPLY STOPS AND CHECK VALVES. ACCESSORIES: V-70 EXTRUDED VINYL BUMPER GUARDS ON EXPOSED SIDES, T-35 36" RUBBER HOSE WITH STAINLESS STEEL WALL BRACKET.	1/2"	1/2"	3"	2"
FD-1	FLOOR DRAIN	SIOUX CHIEF	833-225NR (ROUND) 833-225NQ (SQUARE)	GENERAL PURPOSE CAST IRON BODY WITH FLASHING COLLAR, ADJUSTABLE STRAINER HEAD, ROUND NICKEL BRONZE STRAINER, AND SEEPAGE OPENINGS. OUTLET SIZE PER PLANS. PROVIDE WITH SQUARE GRATE WHERE DRAIN IS INSTALLED IN TILE FLOORS. NOTE: PROVIDE WITH TRAP PRIMER CONNECTION WHERE REQUIRED BY LOCAL CODE OR AS INDICATED ON DRAWINGS.	-	-	2"	1-1/2"

**WATER HEATER SCHEDULE (ELECTRIC)**


MARK	MANUFACTURER	MODEL	TANK LINING	TANK CAPACITY (GAL)	RECOVERY	INPUT (KW)	THERMAL EXPANSION TANK MODEL NO.	NOTES	ELECTRICAL						
									VOLT	PHASE	HZ	FLA	MOCP	DISCONNECT	NOTES
DWH-1	AO SMITH	DEL-20	GLASS	20	10 GPM @ 80°F	2	PLT-5	1,2	208	1	60	9.6	15	NA	A

NOTES:  
1. PROVIDE WITH TEMPERATURE AND PRESSURE RELIEF VALVE AND DRAIN.  
2. PROVIDE WITH CONTROL THERMAL EXPANSION TANK, WATTS MODEL, SCHEDULED WITH WATTS SCV SERVICE CHECK VALVE.

NOTES:  
A. PANEL IS IN THE SAME ROOM WITH THE WATER HEATER

**NOTES:**


- PROVIDE PRESSURE REGULATOR, SET TO 75 PSI WHERE SOURCE PRESSURE EXCEEDS 80 PSI. INSTALL DOWNSTREAM OF BACKFLOW PREVENTER OUTLET.
- ARRANGEMENT SHOWN IS SCHEMATIC. MODIFY TO SUIT CONDITIONS. INSTALL SO BFP CAN BE SERVICED AND TESTED IN ACCORDANCE W/ ALL RULES & REGULATIONS OF LOCAL AUTHORITIES.
- ROUTE DRAIN AS INDICATED ON PLANS.
- SUPPORT AS REQUIRED FROM SLAB.



**INTERIOR BACKFLOW PREVENTER DETAIL**  
NO SCALE (FOR PIPE SIZES 2" OR LESS)

**NOTES:**

- CONTRACTOR TO INSTALL WHERE INDICATED ON PLANS IN ACCESSIBLE LOCATION.
- INSTALL PER MANUFACTURERS RECOMMENDATIONS.
- WATER HEATERS THAT ARE NOT RECIRCULATED SHALL BE EQUIPPED WITH AN INLET AND OUTLET HEAT TRAP, WHETHER INTEGRAL OR EXTERNAL, IN ACCORDANCE WITH THE IECC ENERGY CODE.
- FOR DOMESTIC WATER SYSTEMS UTILIZING PVC, CPVC OR PEX, PROVIDE 18" MINIMUM COPPER OR BREADED STAINLESS STEEL HOSE CONNECTIONS.




**ELECTRIC WATER HEATER DETAIL**  
NO SCALE



924 FRANCIS ST.  
ST. JOSEPH, MO 64501  
P: 816-233-8003 F: 816-233-7793  
www.ellison-auxier.com

CONSULTANTS



+ associates  
1730 Walnut Street Kansas City, Missouri 64108  
1915 Frederick Avenue, St. Joseph, Missouri 64501  
Phone: 816.221.1411 | Fax: 816.221.1429  
LANKFORD | FENDLER + ASSOCIATES, CONSULTING ENGINEERS, INC.  
COPYRIGHT © 2024

NO. ISSUE DESCRIPTION DATE

NO. REVISION DESCRIPTION DATE

NOT FOR CONSTRUCTION

PROJECT:  
MISSOURI WESTERN  
STATE UNIVERSITY  
MERCHANDISE BUILDING

Enter address here

PLUMBING PLAN

SHEET:  
**P100**

OF: DATE: Issue Date

